



ES14-12

SPECIFICATIONS

Nominal Voltage (V) 12V

Nominal Capacity

20 hour rate (0.7A to 10.50V)	14.0Ah
10 hour rate (1.4A to 10.50V)	13.3Ah
5 hour rate (2.38A to 10.20V)	11.9Ah
1C (14A to 9.60V)	8.87Ah
3C (42A to 9.60V)	5.6Ah

Weight Approx. 9.42Lbs. (4.28kg)

Internal Resistance (at 1KHz) 9 mΩ

Maximum Discharge Current for 5 seconds : 135A

Operating Temperature Range

Charge	-15°C (5°F) to 40°C (104°F)
Discharge	-15°C (5°F) to 50°C (122°F)
Storage	-15°C (5°F) to 40°C (104°F)

Charge Retention (shelf life) at 20°C (68°F)

1 month	98%
3 months	94%
6 months	85%

Charging Methods at 20°C (68°F)

Cycle Use : Charging Voltage 14.4 to 15.0V
Maximum Charging Current : 4.2A

Standby Use : Float Charging Voltage 13.50 to 13.80V

Life expectancy :

Cycle Use :	100% depth of discharge	225 cycles
	80% depth of discharge	250 cycles
	50% depth of discharge	750 cycles

Standby Use : 3-5 years




Case Material : ABS
(Option : 94-HB & 94V-0 Flame Retardant Case Material)

Terminal : F2

Maintenance-Free Rechargeable Sealed Lead-Acid Battery



DIMENSIONS



MK Battery

1631 South Sinclair Street • Anaheim, California 92806

Toll Free: 800-372-9253 • Fax: 714-937-0818 • E-mail: sales@mkbattery.com

