



ES17-12

SPECIFICATIONS

Nominal Voltage (V) 12V

Nominal Capacity

20 hour rate (0.9A to 10.50V)	18Ah
10 hour rate (1.8A to 10.50V)	17.1Ah
5 hour rate (3.06A to 10.20V)	15.3Ah
1C (18A to 9.60V)	8.1Ah
3C (54A to 9.60V)	6.3Ah

Weight Approx. 13.82Lbs. (6.28kg)

Internal Resistance (at 1KHz) 10 mΩ

Maximum Discharge Current for 30 seconds : 360A

Maximum Discharge Current for 5 seconds : 720A

Operating Temperature Range

Charge	0°C (32°F) to 40°C (104°F)
Discharge	-15°C (5°F) to 50°C (122°F)
Storage	-15°C (5°F) to 40°C (104°F)

Charge Retention (shelf life) at 20°C (68°F)

1 month	92%
3 months	90%
6 months	80%

Charging Methods at 20°C (68°F)

Cycle Use : Charging Voltage 14.4 to 15.0V
Maximum Charging Current : 5.4A

Standby Use : Float Charging Voltage 13.50 to 13.80V

Life expectancy :

Cycle Use :	100% depth of discharge 200 cycles
	80% depth of discharge 225 cycles
	50% depth of discharge 500 cycles

Standby Use : 3-5 years

Case Material :

ABS
(Option : 94-HB & 94V-0 Flame Retardant Case Material)

Terminal :




F2 or F3

Maintenance-Free Rechargeable Sealed Lead-Acid Battery



DIMENSIONS

mm(inch)



MK Battery

1631 South Sinclair Street • Anaheim, California 92806

Toll Free: 800-372-9253 • Fax: 714-937-0818 • E-mail: sales@mkbattery.com



Solicítenos presupuesto sin compromiso: +34 952 926 985

