



ES4-6

SPECIFICATIONS

Nominal Voltage (V) 6V

Nominal Capacity

20 hour rate (0.225A to 5.25V)	4.5Ah
10 hour rate (0.45A to 5.25V)	4.275Ah
5 hour rate (0.765A to 5.25V)	3.825Ah
1C (4.5A to 4.80V)	2.025Ah
3C (13.5A to 4.80V)	1.57Ah

Weight Approx. 2.00Lbs. (0.91kg)

Internal Resistance (at 1KHz) 18 mΩ

Maximum Discharge Current for 30 seconds : 90A

Maximum Discharge Current for 5 seconds : 180A

Operating Temperature Range

Charge	0°C (32°F) to 40°C (104°F)
Discharge	-15°C (5°F) to 50°C (122°F)
Storage	-15°C (5°F) to 40°C (104°F)

Charge Retention (shelf life) at 20°C (68°F)

1 month	92%
3 months	90%
6 months	80%

Charging Methods at 20°C (68°F)

Cycle Use : Charging Voltage 7.20 to 7.50V
Maximum Charging Current : 1.35A

Standby Use : Float Charging Voltage 6.75 to 6.90V

Life expectancy :

Cycle Use : 100% depth of discharge 200 cycles
80% depth of discharge 225 cycles
50% depth of discharge 500 cycles

Standby Use : 3-5 years

Case Material : ABS
(Option : 94-HB & 94V-0 Flame Retardant Case Material)


Terminal : F1

Maintenance-Free Rechargeable Sealed Lead-Acid Battery






DIMENSIONS

mm(inch)



F1
(FASTON TAB NO. 187)



MK Battery

1631 South Sinclair Street • Anaheim, California 92806

Toll Free: 800-372-9253 • Fax: 714-937-0818 • E-mail: sales@mkbattery.com



Solicítenos presupuesto sin compromiso: +34 952 926 985

