


Specifications

Nominal Voltage		12V
Rated Capacity (20 hour rate)		40AH
Dimension	Total Height (with terminals)	174mm(6.85inches)
	Height	174mm(6.85 inches)
	Length	198mm(7.80 inches)
	Width	166mm(6.54inches)
Weight		Approx.13.4kg (29.54lbs)


Characteristics

Capacity 77°F (25°C)	20 hour rate (2.0A to 10.5Volts)	40AH
	10 hour rate (3.6A to 10.5Volts)	36AH
	5 hour rate (6.56A to 10.2Volts)	32.8AH
Internal Resistance	Full charged Battery 77°F (25°C)	9 mΩ
Capacity affected by Temperature (20 hour rate)	104°F (40°C)	102%
	77°F (25°C)	100%
	32°F (0°C)	85%
	5°F (-15°C)	65%
Self-Discharge 77°F (25°C)	Capacity after 3 month storage	91%
	Capacity after 6 month storage	82%
	Capacity after 12 month storage	64%
Standard Terminal	M6	
Max. Discharge Current 77°F (25°C)	600A (5s)	
Cranking Performance	Cranking Amps (30-sec amps to 7.2V @ 32° F (0° C))	320
	Cold Cranking Amps (30-sec amps to 7.2V @ 0° F (-18° C))	275
Reserve Capacity (Minutes to 10.5V at 80°F (27°C))	@ 25Amps	53Min
	@ 75Amps	-
Charging (Constant Voltage)	Cycle	Initial Charging Current 8A Or Small 14.5V~14.9V/77°F (25°C)
	Float	13.6V~13.8V/77°F (25°C)

Discharge characteristics 77°F (25°C)



Duration of discharge vs. Discharge current



Constant Current Discharge Rating Amperes @ 77 °F (25°C)

Cut off voltage V/cell	15M	30M	45M	1H	2H	3H	5H	8H	10H	12H	20H	24H
1.75V	60	38	28	22.7	12.0	9.1	6.3	4.4	3.60	3.07	2.00	1.67