



# HC105 SPECIFICATIONS

## BATTERY DESIGN

- Absorbent glass mat (AGM) technology
- 12V battery VRLA
- Can be mounted in any orientation except inverted.
- US DOT and IATA certified non-spillable
- Sealed Construction (Non-Spillable Battery)
- Can be choose to fitted with TP brass automotive terminal
- Shipped fully charged - just install and go!
- Suited for repeated discharges such as running your vehicle with winches or other electrical accessories.

## PERFORMANCE FEATURES

- PHCA: 2150A at 80°F (27°C) for 5 seconds
- PCCA: 1470A at 0°F (-18°C) for 5 seconds
- CCA: 1050A at 0°F (-18°C)
- CA/MCA: 1300A at 32°F (0°C)
- HCA: 1505A at 80°F (27°C)
- Reserve capacity: 242 minutes
- Short circuit current: 5000A
- Operation temperature range: -5°F (-15°C) to 122°F (50°C)

## Nominal Dimensions

Length		Width		Height		Total Height		Weight	
mm	in	mm	in	mm	in	mm	in	kg	pound
328	12.91	172	6.77	214	8.43	220	8.66	34	74.96




## HIGH RATE DISCHARGE AT 77°F (25°C)

5 sec.	10 sec.	20 sec.	30 sec.
2150A	1975A	1700A	1520A

## EXTENDED DISCHARGE AT 77°F (25°C) TO 10.02V

5min	15min	1hr	3hr	5hr	10hr	20hr
425A	210A	72A	30A	20.0A	11.4A	6.0A

## PHYSICAL CHARACTERISTICS



## Terminal

unit:mm

