

# 8G5SHP

## SPECIFICATIONS

Nominal Voltage (V)	12V
*Capacity at C/100	137 Ah
*Capacity at C/20	125 Ah
*Capacity at C/5	110 Ah
Weight	85 lbs. (38.6 kg)
Plate Alloy	Lead Calcium
Posts	Forged Terminals & Bushings
Container/Cover	Polypropylene
Operating Temperature Range	-76°F (-60°C) - 140°F (60°C)
Charge Voltage @ 68°F (20°C)	
Cycle	2.30 - 2.35 VPC
Float	2.25 - 2.30 VPC
Vent	Self-sealing
Electrolyte	Sulfuric acid thixotropic gel
Terminal	(B) T876



Rated UN2794, wet filled with acid

Made in the U.S.A. by East Penn Manufacturing Co, Inc.

\* Capacities are based on peak performance.

## Valve-Regulated, Gelled-Electrolyte Battery




## DIMENSIONS

Inches (mm)

Length	13.58 (345 mm)
Width	6.77 (172 mm)
Height	11.42 (290 mm)

Gel Cycle Life vs Depth of Discharge at +25°C (77°F)  
Based on BCI 2-hour Capacity



MK Battery

1631 South Sinclair Street • Anaheim, California 92806

Toll Free: 800-372-9253 • Fax: 714-937-0818 • E-mail: sales@mkbattery.com

