



# ES26-12

## SPECIFICATIONS

**Nominal Voltage (V)** 12V

### Nominal Capacity

20 hour rate ( 1.3A to 10.50V )	26Ah
10 hour rate ( 2.6A to 10.50V )	24.7Ah
5 hour rate ( 4.42A to 10.20V )	22.1Ah
1C ( 26A to 9.60V )	11.7Ah
3C ( 78A to 9.60V )	9.10Ah

**Weight** Approx. 20.53Lbs. (9.33kg)

**Internal Resistance (at 1KHz)** 8 mΩ

**Maximum Discharge Current for 30 seconds :** 520A

**Maximum Discharge Current for 5 seconds :** 1040A

### Operating Temperature Range

Charge	0°C (32°F) to 40°C (104°F)
Discharge	-15°C (5°F) to 50°C (122°F)
Storage	-15°C (5°F) to 40°C (104°F)

### Charge Retention (shelf life) at 20°C ( 68°F )

1 month	92%
3 months	90%
6 months	80%

### Charging Methods at 20°C ( 68°F )

**Cycle Use :** Charging Voltage 14.4 to 15.0V  
Maximum Charging Current : 7.8A

**Standby Use :** Float Charging Voltage 13.50 to 13.80V

### Life expectancy :

<b>Cycle Use :</b>	100% depth of discharge 200 cycles
	80% depth of discharge 225 cycles
	50% depth of discharge 500 cycles

**Standby Use :** 3-5 years

### Case Material :

ABS  
(Option : 94-HB & 94V-0 Flame Retardant Case Material)

### Terminal :




F2 or F3

## Maintenance-Free Rechargeable Sealed Lead-Acid Battery



## DIMENSIONS

mm(inch)



## MK Battery

1631 South Sinclair Street • Anaheim, California 92806

Toll Free: 800-372-9253 • Fax: 714-937-0818 • E-mail: sales@mkbattery.com

